

SAGOLA 437 PLUS

AIR LUBRICATOR

elcometer®
www.elcometer.com

Sagola 437 Plus

Air Lubricator

Ideal for the proper lubrication of pneumatic tools.

- Safe operation from 3l/min.
- Minimum flow restrictions.
- Multiple inlet and outlet dimensions (1/2", 3/8" and 1/4").
- Oil level check window.
- Manual oil regulator by level check window, drop by drop system.
- CNC machined in solid aluminium.
- Made in aluminium.
- Minimum maintenance.



Sagola 437Plus

TECHNICAL SPECIFICATION

Air Flow (at 7bar air inlet pressure)	1920l/min (67.8cfm)
Maximum Working Pressure	10bar (145psi)
Maximum Operating Temperature	90°C (194°F)
Dimensions (without coupling)	165 x 73 x 73 mm (6.49 x 2.87 x 2.87")
Weight	446g (15.73lbs)
Packing List	Sagola 437 Plus Air Lubricator

Part Numbers	1/2" Inlet	3/8" Inlet	1/4" Inlet
Sagola 437 Plus Air Lubricator	PT10710301	PT10710302	PT10710303

* US-MIL, Euro-profile or NITTO version depending on part number ordered.

Elcometer is a registered trademarks of Elcometer Limited. All other trademarks are acknowledged.

Due to our policy of continuous improvement, Elcometer Limited reserves the right to change specifications without notice.

All products are covered by a comprehensive warranty, for more information visit www.elcometer.com/warranty.

© Elcometer Limited, 2023. All rights reserved. No part of this document may be reproduced, transmitted, stored (in a retrieval system or otherwise), or translated into any language, in any form, or by any means, without the prior written permission of Elcometer Limited.